

SE30-2ML														
SE30-2ML Parameter	Rated Voltage(V)	Battery qty	Rated power(W)	Capacity (t)	Rated Current (A)	Use times(10t)	N.W without extension(kg)	N.W with extension (kg)	G.W(kg)	Packaging Size (L×W×H)		Pallet Size (L×W×H)		qty/pallet
	DC 36V (18V+18V)	2	650	30/15	19	≥40	32	38	48	688×294×188mm		880×690×867mm		12台
	A	B	C	D	E	F	G	M	K1	K2	α	β	Oil Volume (L)	
	652	272	1168	178	150	78	62	700~2000	75	45	45°	10°	0.9	
Battery Parameter	Rated voltage (V)	Charging cut-off voltage (V)	Discharge cut-off voltage (V)	Battery capacity (mAh)	Battery energy (Wh)	Battery internal resistance (mΩ)	Discharge protection current (A)	Charging working temperature (℃)	Discharge operating temperature (℃)	Charging time (h)				
	DC 18V	21.25	13.5	5000	90	≤65	≥63	0~45	-5~55	≤2.5				
Charger Parameter		Input voltage (V)	Input frequency (Hz)	Input power (W)	Charging output current (A)	Charging output voltage (V)	Efficiency	MTBF (h)	Standard					
	EuropeanStandard (GS)	AC 200-240	50-60	≤65	2.3 ± 0.2	DC 11-20.6 ± 0.2	≥80%	≥5000	GS-EN60335					
	USA standard (UL)	AC 100-120	50-60	≤65	2.3 ± 0.2	DC 11-20.6 ± 0.2	≥83%	≥5000	ETL-UL1310					

